Abstract Submitted for the DPP96 Meeting of The American Physical Society

Sorting Category: 4.1 (theoretical)

Backscatter, filamentation and laser light smoothing in flowing plasmas.* D. E. HINKEL, C. H. STILL, R. L. BERGER, A. B. LANGDON, E. A. WILLIAMS, Lawrence Livermore National Laboratory — The three-dimensional (3-D) code F3D with nonlinear hydrodynamics ¹ is used to examine filamentation and backscatter driven by non-uniform laser beams. Previous work with linearized hydrodynamics demonstrated that both supersonic and subsonic transverse flow deflects the laser beam in the flow direction. ² In agreement with analytic estimates, ³ 3-D simulations of uniform, initially stationary plasma show that laser beam RPP hotspots move, yielding a time averaged laser intensity smoother than the instantaneous pattern. This naturally occurring smoothing will be compared to that in two-dimensional simulations. ⁴ The influence of 3-D beam structure on filamentation, Brillouin backscatter and beam smoothing will be examined with and without axial and transverse flow.

D. E. Hinkel
Prefer Oral Session denise@icf.llnl.gov
Prefer Poster Session Lawrence Livermore National Laboratory

Date submitted: July 5, 1996 Electronic form version 1.1

^{*}Work performed under the auspices of the U. S. DOE by LLNL under Contract No. W-7405-ENG-48.

¹C. H. Still et al., BAPS 40, 1823 (1995).

²D. E. Hinkel et al., accepted, PRL, June, 1996.

³D. E. Hinkel and E. A. Williams, BAPS 37, 1376 (1992).

⁴A. J. Schmitt and B. B. Afeyan, BAPS 40. 1824 (1995).